



1a	RING ³⁾	2	STEEL (SS400) WITH EPOXY POWDER COAT.	³⁾ PP Body :Used for 6"~16"
28	BOLT (C)	4	STAINLESS STEEL 304	PVDF Body :Used for 12"~16"
25	GEAR BOX	1	DIECAST ALUMINIUM ALLOY (AC3A) etc.	POWDER COAT.
7	STEM	1	STAINLESS STEEL 316, 403	²⁾ Used for Size 2" ~ 16"
6	O-RING (C)	1	EPDM, FKM, etc.	
5	O-RING (B)	2		
4	O-RING (A) ²⁾	2		
3	SEAT	1		
2	DISC	1	PP, PVDF etc.	¹⁾ PVC Body 1 1/2" ~ 14"
1	BODY ¹⁾	1	PVC, PVDF etc.	
No.	DESCRIPTION	No.REQ'D	MATERIAL	REMARKS

FOR REFERENCE ONLY □
ASAHI/AMERICA

THIS DRAWING AND ALL INFORMATION
HEREON IS THE PROPERTY OF
ASAHI/AMERICA. ANY COPYING,
REPRODUCTION OR UNAUTHORIZED USE
IS FORBIDDEN WITHOUT WRITTEN
CONSENT.

	NAME	DATE
DR	KENICHI MIYAZAKI	8/27/02
APPD	DAVE HURLEY	8/27/02
PROD	LEO LESTER	8/27/02
WO#/SO#		
FILE		

ASAHI/AMERICA

ISO 9001 CERTIFIED

35 GREEN STREET, P.O. BOX 653, MALDEN, MA.



BUTTERFLY VALVE TYPE56
EXPLODED VIEW GEAR TYPE
1-1/2" THRU. 16"

SIZE	A	DWG. NO.	0181BF	REV	c
SCALE	NTS		SHEET 1 OF 1		